

LCD Commercial EV Charger

EU



LCD Commercial EV Charger



Model: EVC332-E1



Features

- OTA Remote Firmware Updates
- OCPP 1.6J Fully Compliance
- 4.3" LCD Screen

Application

- Commercial Area
- Public Parking Garage
- Residential Area

Suitable for EU



	16A Max	32A Max	16A Max	32A Max
Electrical Parameter	Single phase input: 230VAC 50-60 Hz		Three phase input: 3 × 230VAC 50-60 Hz	
	3.7kW at 230VAC	7.4kW at 230 VAC	11 kW at 3 × 230 VAC	22 kW at 3 × 230 VAC
Input Cord	Hardwired			
Output Cable & Connector	16.4FT/5.0 m cable (26.2FT/8.0m optional)			
	IEC62196-2 standard compliance			
Environmental Parameter	Protection Class IP65: Weatherproof, dust-tight			
	IK08: Resistant polycarbonate case			
	Operating Temperature: -22°F to 122°F (-30°C to 50°C)			
Dimension	Main Enclosure: 9.7in x 12.8in x 3.8in (247mm × 326mm × 97mm)			
Standards	IEC 61851-1, IEC61851-21-2, IEC62196-2, OCPP 1.6J compliance			
Certification	CE, UKCA, SAA Listed			

Optional

- 4G Module
- Socket
- Power balance EMS
- Color customization