

LCD Home EV Charger

NA



LCD Home EV Charger



Model: EVR48-N3



Bluetooth Wi-Fi APP

Features

- OTA Remote Firmware Updates
- 4.3" LCD Screen
- Enclosure Rating: NEMA Enclosure Type 4

Application

- Residential Area

Suitable for NA



	32A Max	40A Max	48A Max	80A Max
Electrical Parameter	Single phase input: 208-240VAC 60 Hz			
	7.6kW at 240 VAC	9.6kW at 240 VAC	11.5kW at 240 VAC	19.2kW at 240 VAC
Input Cord	NEMA 14-50 or NEMA 6-50 Electrical Plug		Hardwired	
Output Cable & Connector	18 FT/5.5 m cable (25 FT/7.5m optional)			
	SAE J1772, NACS standard compliance			
Environmental Parameter	NEMA Enclosure Type4: Weatherproof, dust-tight			
	IK08: Resistant polycarbonate case			
	Operating Temperature: -22°F to 122°F (-30°C to 50°C)			
Dimension	Main enclosure: 12.8in × 9.7in × 3.8in (326mm × 247mm × 97mm)			
Standards	NEC625, UL2231, UL2594, ISO15118 compliance			
Certification	ETL, FCC, Energy Star compliance			

Optional

- RFID
- Power balance EMS
- Color customization