



Features:

- Cost Effective Solution
- Environmental Friendly
- Compact Size for Easy Storage
- Fast Charging—Utilizing the Standard J1772 Charging Protocol



	10A Max	16A Max	32A Max	40A Max
Electrical Parameter	2.4kW at 240 VAC	3.8kW at 240 VAC	7.6kW at 240 VAC	9.6kW at 240 VAC
	Single phase input: nominal voltage 208-240 VAC 60 Hz			
Input Cord	0.98 FT / 300mm NEMA 5-15P			
	0.98 FT / 300mm NEMA 6-50P			
	0.98 FT / 300mm NEMA 14-50P			
Output Cable & Connector	18 FT / 5.5m cable (25 FT / 7.5m optional)			
	SAE J1772 Compliant, Type 1 Plug			
Smart Grid Connectivity (Optional)	Built-in WIFI / Bluetooth Connectivity, compatible with Tuya platform			
Environmental Parameter	Encloser NEMA Type 3, EV Charger NEMA Type 3R			
	Free-installation (charge with the car)			
	Operating Temperature: -22°F to 122°F (-30°C to 50°C)			
Dimension	Main enclosure: 9.7 in × 4.6 in × 2.6 in (247 mm × 118 mm × 66 mm)			
Codes & Standards	UL991, UL2251			
Safety	Meet the requirements of FCC standards			
Warranty	1 year limited product warranty			