

产品介绍 product description



直臂 Full Overlay






中弯 Half Overlay



大弯 Inset

底座安装孔位与盖位表 Installation hole location



$H=14+K-D$

D \ K	3	4	5	6	7
0	17	18	19	20	21
2	15	16	17	18	19
4	13	14	15	16	17


$H=5+K-D$

D \ K	3	4	5	6	7
0	8	9	10	11	12
2	6	7	8	9	10
4	4	5	6	7	8


$H=-5+K-D$

D \ K	3	4	5	6	7
0	-2	-1	0	1	2
2	-4	-3	-2	-1	0
4	-6	-5	-4	-3	-2


铰杯安装孔位尺寸 Installation hole location



孔距:45mm



孔距:48mm



孔距:52mm

YD-402 40杯液压固装铰链

Fixed hydraulic hinge



开门角度:95°
 适用门板厚度:14-24mm
 门板K距离:3-7mm
 原材料:铁
 工序:电镀
 杯孔尺寸:48mm(45mm/52mm)
 杯直径/深:40mm/11.5mm
 性能:深度调节±2毫米、高度调节±2毫米、盖门调节+4毫米
 Opening angle:95°
 Door thickness:14-24mm
 Door (K) dimension:3-7mm
 Material:iron
 Surface:nickle
 Hole distance:48mm(45mm/52mm)
 Diameter/depth of hinge cup:40mm/11.5mm
 Function:the depth regulate ±2millimeters、Regulate ±2millimeters highly、Covering the door regulates +4millimeter