

产品介绍 product description



直臂 Full Overlay






中弯 Half Overlay



大弯 Inset

底座安装孔位与盖位表 Installation hole location



$H=14+K-D$

D	K	3	4	5	6	7
H						
0		17	18	19	20	21
2		15	16	17	18	19
4		13	14	15	16	17


$H=5+K-D$

D	K	3	4	5	6	7
H						
0		8	9	10	11	12
2		6	7	8	9	10
4		4	5	6	7	8


$H=-5+K-D$

D	K	3	4	5	6	7
H						
0		-2	-1	0	1	2
2		-4	-3	-2	-1	0
4		-6	-5	-4	-3	-2


铰杯安装孔位尺寸 Installation hole location



孔距:45mm



孔距:48mm



孔距:52mm

YD-699 35杯液压固装铰链

Fixed hydraulic hinge



开门角度:100°
 适用门板厚度:14-20mm
 门板K距离:3-7mm
 原材料:冷轧钢
 工序:镀铜镀镍
 杯孔尺寸:48mm(45mm/52mm)
 杯直径/深:35mm/11.5mm
 性能:盖位调节-4~1mm,间隙调节-3~4mm,底座上下调节+/-2mm,
 具有小角度开启缓冲功能,小角度值为开门10° +/-1°
 Opening angle:100°
 Door thickness:14-20mm
 Door (K) dimension:3-7mm
 Material:cold-rolled steel
 Surface:copper&Nickel plated
 Hole distance:48mm(45mm/52mm)
 Diameter/depth of hinge cup:35mm/11.5mm
 Function:Overlay Adjustment -4mm-1mm
 Gap adjustment -3mm-4mm Up/Down Adjustment +/-2mm Having buffering effect,
 when opening angel as small as 10° +/-1°