

产品介绍 product description



直臂 Full Overlay




中弯 Half Overlay




大弯 Inset

底座安装孔位与盖位表 Installation hole location




$$H=14+K-D$$

D	K	3	4	5	6	7
H	0	17	18	19	20	21
2	15	16	17	18	19	
4	13	14	15	16	17	



$$H=5+K-D$$


D	K	3	4	5	6	7
H	0	8	9	10	11	12
2	6	7	8	9	10	
4	4	5	6	7	8	




$$H=-2+K+A$$

D	K	3	4	5	6	7
H	0	-1	-2	-3	-4	-5
2	1	0	-1	-2	-3	
4	3	2	1	0	-1	


铰杯安装孔位尺寸 Installation hole location



孔距:45mm



孔距:48mm



孔距:52mm

YD-6165 165°液压固装铰链 Hydraulic fixed hinge



开门角度:165°
杯材料:铁镀镍
杯尺寸:35mm 深:11.5mm
杯孔尺寸:48mm
杯安装尺寸:木牙螺丝M4*16mm
性能:深度调节±2毫米、高度调节±2毫米、盖门调节+4毫米

Opening angle:165°
Cup material:Steel nickel plated
Cup diameter:35mm Depth:11.5mm
Hole pitch:48mm
Cup fixed:Wood screws M4*16mm
Function:the depth regulate ±2millimeters, Regulate ±2millimeters highly,
Covering the door regulates +4millimeter