

## 产品介绍 product description



直臂 Full Overlay






中弯 Half Overlay



大弯 Inset

## 底座安装孔位与盖位表 Installation hole location



$H=14+K-D$  ( $K=4$ , 最大盖位可盖到  $D=20$ )

| D \ K | 3  | 4  | 5  | 6  | 7  |
|-------|----|----|----|----|----|
| 0     | 17 | 18 | 19 | 20 | 21 |
| 2     | 15 | 16 | 17 | 18 | 19 |
| 4     | 13 | 14 | 15 | 16 | 17 |


$H=5+K-D$

| D \ K | 3 | 4 | 5  | 6  | 7  |
|-------|---|---|----|----|----|
| 0     | 8 | 9 | 10 | 11 | 12 |
| 2     | 6 | 7 | 8  | 9  | 10 |
| 4     | 4 | 5 | 6  | 7  | 8  |


$H=-5+K-D$

| D \ K | 3  | 4  | 5  | 6  | 7  |
|-------|----|----|----|----|----|
| 0     | -2 | -1 | 0  | 1  | 2  |
| 2     | -4 | -3 | -2 | -1 | 0  |
| 4     | -6 | -5 | -4 | -3 | -2 |


## 铰杯安装孔位尺寸 Installation hole location



孔距:45mm



孔距:48mm



孔距:52mm

## YD-G622 35杯液压固装铰链

Fixed hydraulic hinge



开门角度:102°  
 适用门板厚度:14-20mm  
 门板K距离:3-7mm  
 原材料:冷轧钢  
 工序:镀铜镀镍  
 杯孔尺寸:48mm (45mm/52mm)  
 杯直径/深:35mm/11.5mm  
 性能:深度调节±3.5毫米、高度调节±2.0毫米、盖门调节+2~-4mm毫米  
 Opening angle:102°  
 Door thickness:14-20mm  
 Door (K) dimension:3-7mm  
 Material:cold-rolled steel  
 Surface:copper&Nickel plated  
 Hole distance:48mm (45mm/52mm)  
 Diameter/depth of hinge cup:35mm/11.5mm  
 Function:the depth regulate ±3.5millimeters, Regulate ±2.0millimeters highly,  
 Covering the door regulates +2~-4millimeter