

产品介绍 product description



直臂 Full Overlay






中弯 Half Overlay



大弯 Inset

底座安装孔位与盖位表 Installation hole location



H=14+K-D

D \ K	3	4	5	6	7
0	17	18	19	20	21
2	15	16	17	18	19
4	13	14	15	16	17


H=5+K-D

D \ K	3	4	5	6	7
0	8	9	10	11	12
2	6	7	8	9	10
4	4	5	6	7	8


H=5+K-D

D \ K	3	4	5	6	7
0	-2	-1	0	1	2
2	-4	-3	-2	-1	0
4	-6	-5	-4	-3	-2


铰杯安装孔位尺寸 Installation hole location



孔距:45mm



孔距:48mm



孔距:52mm

YD-P622 35杯液压快装铰链

Clip on hydraulic hinge



开门角度:102°
 适用门板厚度:14-20mm
 门板K距离:3-7mm
 原材料:冷轧钢
 工序:镀铜镀镍
 杯孔尺寸:48mm(45mm/52mm)
 杯直径/深:35mm/11.5mm
 性能:深度调节±3.5毫米、高度调节±2.0毫米、盖门调节+1~4毫米
 Opening angle:102°
 Door thickness:14-20mm
 Door (K) dimension:3-7mm
 Material:cold-rolled steel
 Surface:copper&Nickel plated
 Hole distance:48mm(45mm/52mm)
 Diameter/depth of hinge cup:35mm/11.5mm
 Function:the depth regulate ±3.5millimeters, Regulate ±2.0millimeters highly,
 Covering the door regulates +1~4millimeter