

产品介绍 product description



直臂 Full Overlay






中曲 Half Overlay



大曲 Inset

底座安装孔位与盖位表 Installation hole location



H=14+K-D(K=4,最大盖位可盖到D=19)

D	K	3	4	5	6	7
H	0	17	18	19	20	21
2	15	16	17	18	19	
4	13	14	15	16	17	


H=5+K-D

D	K	3	4	5	6	7
H	0	8	9	10	11	12
2	6	7	8	9	10	
4	4	5	6	7	8	


H=-5+K-D

D	K	3	4	5	6	7
H	0	-2	-1	0	1	2
2	-4	-3	-2	-1	0	
4	-6	-5	-4	-3	-2	


铰杯安装孔位尺寸 Installation hole location



孔距:45mm



孔距:48mm



孔距:52mm

YOU^UDO YD-G625 二段力35杯液压固装铰链 Fixed hydraulic hinge



开门角度:105°
适用门板厚度:14-24mm
门板K距离:3-7mm
原材料:铁
工序:镀镍
杯孔尺寸:48mm(45mm/52mm)
杯直径/深:40mm/11.5mm
性能:深度调节±3毫米、高度调节±2毫米、盖门调节+1~4毫米
Opening angle:105°
Door thickness:14-24mm
Door (K) dimension:3-7mm
Material:iron
Surface:nickle
Hole distance:48mm(45mm/52mm)
Diameter/depth of hinge cup:40mm/11.5mm
Function:the depth regulate ±3millimeters、Regulate ±2millimeters highly、Covering the door regulates +1~4millimeter

YD-G625

二段力

二段力, 闭合45度即可二段力停留

防止开门用力过猛使铰链严重受压导致主体变形和螺丝松脱

CAN STOP ANYWHERE

柜门开启45°后可在任意位置停下