



Indoor Luminaire Photometric Data

Description Information

Luminary Name: 55252		Lum. Catalog:	Test ID:
Lamp Name:		Lamp Catalog:	Test Date: 2023/10/24
Manufacture:		Shld. Ang(°):	Test Machine:GON-2000
Test Lab:		Frequency (Hz):	Lamp CCT (K): Ra:
Lum. Size(W*L*H):0.050m*-0.050m*0.000m		Lum. Area (m2):0.002	Lum. W (kg): 0.000
Test System: C, γ	Test Step: C=30.0 γ=1.0	Temp. (°C): 25	Humidity(%): 50.0


Character Parameter

Lamp Speciality Parameter		Luminaire Speciality Parameter	
Rated Flux(lm): 928.940	Luminary Flux(lm): 928.944	Field Angle(10%Imax): 37.5(°)	
Rated Power(W): 10	Luminary Efficiency: 100.00%	Down Lumens&Percent: 928.944lm 100.00%	
Rated Voltage(V): 220	Luminary EER(lm/W): 86.253	Up Lumens&Percent: 0.000lm 0.00%	
Tested Power(W): 10.770	Max. Candela(cd): 6232.423	S/MH: C0_a180=0.260 C90_270=0.260	
Lamps' Inside: 1	Max Cand@Ang. (°): C=240.0 γ=1.0	CIE Type: Semi-Direct	
Tested Electrics(V, A, pf):223.8, 0.050, 0.960	Beam Angle(50%Imax): 14.9(°)	ErP Φ use(90°): 870.673lm	
Lamp Size(W*L*H):0.050m*-0.050m*0.000m	Left=-6.5°, Right=8.4°	IRF(%): 1491.061	



2D Plane Light Intensity Distribution Curve

Lum. Name: 55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2023/10/24




Photometric Filename:FL-10W-COB-1000-1H-15度.IES

3D Light Intensity Distribution Modal

Lum. Name: 55252	Lum. Catelog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2023/10/24

3D Light Intensity Distribution Modal



Curves: 3D Model — Fixture — Vert. HUD — Hori. HUD —

View Angles: Orient:0 Tilt:0 Roll:0 Spin:0

IES Indoor Report

Photometric Filename:FL-10W-COB-1000-1H-15度.IES

Zonal Flux Tabulation									
Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	5.83	5.83	0.63	0.63	47.0-48.0	4.31	881.34	0.46	94.88
1.0-2.0	17.17	23.00	1.85	2.48	48.0-49.0	4.07	885.41	0.44	95.31
2.0-3.0	27.45	50.46	2.96	5.43	49.0-50.0	3.83	889.24	0.41	95.73
3.0-4.0	36.01	86.46	3.88	9.31	50.0-51.0	3.60	892.84	0.39	96.11
4.0-5.0	42.22	128.68	4.54	13.85	51.0-52.0	3.39	896.22	0.36	96.48
5.0-6.0	45.65	174.33	4.91	18.77	52.0-53.0	3.18	899.41	0.34	96.82
6.0-7.0	46.21	220.54	4.97	23.74	53.0-54.0	2.99	902.40	0.32	97.14
7.0-8.0	44.29	264.83	4.77	28.51	54.0-55.0	2.81	905.20	0.30	97.44
8.0-9.0	40.70	305.53	4.38	32.89	55.0-56.0	2.62	907.83	0.28	97.73
9.0-10.0	36.50	342.03	3.93	36.82	56.0-57.0	2.44	910.27	0.26	97.99
10.0-11.0	32.61	374.64	3.51	40.33	57.0-58.0	2.27	912.54	0.24	98.23
11.0-12.0	29.57	404.21	3.18	43.51	58.0-59.0	2.10	914.64	0.23	98.46
12.0-13.0	27.51	431.72	2.96	46.47	59.0-60.0	1.94	916.58	0.21	98.67
13.0-14.0	26.14	457.86	2.81	49.29	60.0-61.0	1.78	918.35	0.19	98.86
14.0-15.0	25.22	483.08	2.71	52.00	61.0-62.0	1.63	919.98	0.18	99.04
15.0-16.0	24.56	507.64	2.64	54.65	62.0-63.0	1.48	921.46	0.16	99.19
16.0-17.0	23.95	531.59	2.58	57.22	63.0-64.0	1.34	922.80	0.14	99.34
17.0-18.0	23.25	554.83	2.50	59.73	64.0-65.0	1.21	924.01	0.13	99.47
18.0-19.0	22.40	577.24	2.41	62.14	65.0-66.0	1.07	925.08	0.12	99.58
19.0-20.0	21.42	598.66	2.31	64.45	66.0-67.0	0.93	926.01	0.10	99.68
20.0-21.0	20.33	618.98	2.19	66.63	67.0-68.0	0.78	926.79	0.08	99.77
21.0-22.0	19.19	638.17	2.07	68.70	68.0-69.0	0.64	927.43	0.07	99.84
22.0-23.0	18.05	656.22	1.94	70.64	69.0-70.0	0.51	927.94	0.05	99.89
23.0-24.0	16.96	673.18	1.83	72.47	70.0-71.0	0.39	928.33	0.04	99.93
24.0-25.0	15.93	689.11	1.71	74.18	71.0-72.0	0.28	928.61	0.03	99.96
25.0-26.0	14.96	704.07	1.61	75.79	72.0-73.0	0.18	928.79	0.02	99.98
26.0-27.0	14.04	718.11	1.51	77.30	73.0-74.0	0.10	928.90	0.01	100.00
27.0-28.0	13.19	731.30	1.42	78.72	74.0-75.0	0.04	928.94	0.00	100.00
28.0-29.0	12.39	743.69	1.33	80.06	75.0-76.0	0.00	928.94	0.00	100.00
29.0-30.0	11.65	755.34	1.25	81.31	76.0-77.0	0.00	928.94	0.00	100.00
30.0-31.0	10.95	766.29	1.18	82.49	77.0-78.0	0.00	928.94	0.00	100.00
31.0-32.0	10.30	776.59	1.11	83.60	78.0-79.0	0.00	928.94	0.00	100.00
32.0-33.0	9.68	786.27	1.04	84.64	79.0-80.0	0.00	928.94	0.00	100.00
33.0-34.0	9.09	795.36	0.98	85.62	80.0-81.0	0.00	928.94	0.00	100.00
34.0-35.0	8.54	803.91	0.92	86.54	81.0-82.0	0.00	928.94	0.00	100.00
35.0-36.0	8.05	811.96	0.87	87.41	82.0-83.0	0.00	928.94	0.00	100.00
36.0-37.0	7.60	819.56	0.82	88.23	83.0-84.0	0.00	928.94	0.00	100.00
37.0-38.0	7.19	826.75	0.77	89.00	84.0-85.0	0.00	928.94	0.00	100.00
38.0-39.0	6.80	833.55	0.73	89.73	85.0-86.0	0.00	928.94	0.00	100.00
39.0-40.0	6.44	839.99	0.69	90.42	86.0-87.0	0.00	928.94	0.00	100.00
40.0-41.0	6.11	846.10	0.66	91.08	87.0-88.0	0.00	928.94	0.00	100.00
41.0-42.0	5.80	851.90	0.62	91.71	88.0-89.0	0.00	928.94	0.00	100.00
42.0-43.0	5.52	857.42	0.59	92.30	89.0-90.0	0.00	928.94	0.00	100.00
43.0-44.0	5.26	862.68	0.57	92.87	90.0-91.0	0.00	928.94	0.00	100.00
44.0-45.0	5.02	867.70	0.54	93.41	91.0-92.0	0.00	928.94	0.00	100.00
45.0-46.0	4.78	872.48	0.51	93.92	92.0-93.0	0.00	928.94	0.00	100.00
46.0-47.0	4.55	877.03	0.49	94.41	93.0-94.0	0.00	928.94	0.00	100.00

IES Indoor Report


Photometric Filename:FL-10W-COB-1000-1H-15度.IES

Zonal Flux Tabulation - (Cont.)

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94. 0-95. 0	0. 00	928. 94	0. 00	100. 00	141. 0-142. 0	0. 00	928. 94	0. 00	100. 00
95. 0-96. 0	0. 00	928. 94	0. 00	100. 00	142. 0-143. 0	0. 00	928. 94	0. 00	100. 00
96. 0-97. 0	0. 00	928. 94	0. 00	100. 00	143. 0-144. 0	0. 00	928. 94	0. 00	100. 00
97. 0-98. 0	0. 00	928. 94	0. 00	100. 00	144. 0-145. 0	0. 00	928. 94	0. 00	100. 00
98. 0-99. 0	0. 00	928. 94	0. 00	100. 00	145. 0-146. 0	0. 00	928. 94	0. 00	100. 00
99. 0-100. 0	0. 00	928. 94	0. 00	100. 00	146. 0-147. 0	0. 00	928. 94	0. 00	100. 00
100. 0-101. 0	0. 00	928. 94	0. 00	100. 00	147. 0-148. 0	0. 00	928. 94	0. 00	100. 00
101. 0-102. 0	0. 00	928. 94	0. 00	100. 00	148. 0-149. 0	0. 00	928. 94	0. 00	100. 00
102. 0-103. 0	0. 00	928. 94	0. 00	100. 00	149. 0-150. 0	0. 00	928. 94	0. 00	100. 00
103. 0-104. 0	0. 00	928. 94	0. 00	100. 00	150. 0-151. 0	0. 00	928. 94	0. 00	100. 00
104. 0-105. 0	0. 00	928. 94	0. 00	100. 00	151. 0-152. 0	0. 00	928. 94	0. 00	100. 00
105. 0-106. 0	0. 00	928. 94	0. 00	100. 00	152. 0-153. 0	0. 00	928. 94	0. 00	100. 00
106. 0-107. 0	0. 00	928. 94	0. 00	100. 00	153. 0-154. 0	0. 00	928. 94	0. 00	100. 00
107. 0-108. 0	0. 00	928. 94	0. 00	100. 00	154. 0-155. 0	0. 00	928. 94	0. 00	100. 00
108. 0-109. 0	0. 00	928. 94	0. 00	100. 00	155. 0-156. 0	0. 00	928. 94	0. 00	100. 00
109. 0-110. 0	0. 00	928. 94	0. 00	100. 00	156. 0-157. 0	0. 00	928. 94	0. 00	100. 00
110. 0-111. 0	0. 00	928. 94	0. 00	100. 00	157. 0-158. 0	0. 00	928. 94	0. 00	100. 00
111. 0-112. 0	0. 00	928. 94	0. 00	100. 00	158. 0-159. 0	0. 00	928. 94	0. 00	100. 00
112. 0-113. 0	0. 00	928. 94	0. 00	100. 00	159. 0-160. 0	0. 00	928. 94	0. 00	100. 00
113. 0-114. 0	0. 00	928. 94	0. 00	100. 00	160. 0-161. 0	0. 00	928. 94	0. 00	100. 00
114. 0-115. 0	0. 00	928. 94	0. 00	100. 00	161. 0-162. 0	0. 00	928. 94	0. 00	100. 00
115. 0-116. 0	0. 00	928. 94	0. 00	100. 00	162. 0-163. 0	0. 00	928. 94	0. 00	100. 00
116. 0-117. 0	0. 00	928. 94	0. 00	100. 00	163. 0-164. 0	0. 00	928. 94	0. 00	100. 00
117. 0-118. 0	0. 00	928. 94	0. 00	100. 00	164. 0-165. 0	0. 00	928. 94	0. 00	100. 00
118. 0-119. 0	0. 00	928. 94	0. 00	100. 00	165. 0-166. 0	0. 00	928. 94	0. 00	100. 00
119. 0-120. 0	0. 00	928. 94	0. 00	100. 00	166. 0-167. 0	0. 00	928. 94	0. 00	100. 00
120. 0-121. 0	0. 00	928. 94	0. 00	100. 00	167. 0-168. 0	0. 00	928. 94	0. 00	100. 00
121. 0-122. 0	0. 00	928. 94	0. 00	100. 00	168. 0-169. 0	0. 00	928. 94	0. 00	100. 00
122. 0-123. 0	0. 00	928. 94	0. 00	100. 00	169. 0-170. 0	0. 00	928. 94	0. 00	100. 00
123. 0-124. 0	0. 00	928. 94	0. 00	100. 00	170. 0-171. 0	0. 00	928. 94	0. 00	100. 00
124. 0-125. 0	0. 00	928. 94	0. 00	100. 00	171. 0-172. 0	0. 00	928. 94	0. 00	100. 00
125. 0-126. 0	0. 00	928. 94	0. 00	100. 00	172. 0-173. 0	0. 00	928. 94	0. 00	100. 00
126. 0-127. 0	0. 00	928. 94	0. 00	100. 00	173. 0-174. 0	0. 00	928. 94	0. 00	100. 00
127. 0-128. 0	0. 00	928. 94	0. 00	100. 00	174. 0-175. 0	0. 00	928. 94	0. 00	100. 00
128. 0-129. 0	0. 00	928. 94	0. 00	100. 00	175. 0-176. 0	0. 00	928. 94	0. 00	100. 00
129. 0-130. 0	0. 00	928. 94	0. 00	100. 00	176. 0-177. 0	0. 00	928. 94	0. 00	100. 00
130. 0-131. 0	0. 00	928. 94	0. 00	100. 00	177. 0-178. 0	0. 00	928. 94	0. 00	100. 00
131. 0-132. 0	0. 00	928. 94	0. 00	100. 00	178. 0-179. 0	0. 00	928. 94	0. 00	100. 00
132. 0-133. 0	0. 00	928. 94	0. 00	100. 00	179. 0-180. 0	0. 00	928. 94	0. 00	100. 00
133. 0-134. 0	0. 00	928. 94	0. 00	100. 00					
134. 0-135. 0	0. 00	928. 94	0. 00	100. 00					
135. 0-136. 0	0. 00	928. 94	0. 00	100. 00					
136. 0-137. 0	0. 00	928. 94	0. 00	100. 00					
137. 0-138. 0	0. 00	928. 94	0. 00	100. 00					
138. 0-139. 0	0. 00	928. 94	0. 00	100. 00					
139. 0-140. 0	0. 00	928. 94	0. 00	100. 00					
140. 0-141. 0	0. 00	928. 94	0. 00	100. 00					

Rectangle ISO Lighting Intensity Diagram

Lum. Name:55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2023/10/24




Maximum Light Intensity(cd): 6232.42
Maximum Cand.@Angle: H=-0.5°,V=-0.9°

Photometric Filename:FL-10W-COB-1000-1H-15度.IES

Plane ISO-Illuminance Diagram

Lum. Name: 55252	Lum. Catelog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2023/10/24

Plane ISO-Illuminance Curve



Working Plane Luminaire Mounting Height(m): 3.00


Working Plane Maximum Illuminance(lx): 692.18

Working Plane Maximum Illuminance Position(d/h):H-0.0 V-0.0

3D Plane ISO Illuminance Diagram

Lum. Name:55252	Lum. Catelog:	Test ID:
Lamp Name:	Lamp Catelog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2023/10/24


3D Plane Illuminance Modal



Space ISO Illuminance Diagram

Lum. Name:55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2023/10/24


Space ISO Illuminance Curve



Space Plane Maximum Illuminance and @Angle:6116.13lx,0.0deg
Plane Maximum Lighting Intensity and @Angle:6116.125cd,0deg

Illuminance-Distance Diagram

Lum. Name: 55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2023/10/24



Indoor Luminance Limiting Curves

Lum. Name:55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2023/10/24


Glare Grade Table

GI	Quality	Using Illuminance							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama (deg)	45	50	55	60	65	70	75	80	85
C0	39970	30943	23713	16897	11029	4662	0	0	0
C90	44098	33202	25392	19005	12996	2788	0	0	0


Luminance Limiting Curve



Luminous Size: Length(m)=-0.050 Width(m)=-0.050 Height(m)=0.000 Area(m^2)=0.001963
Luminous Type: Without Luminous Side
Luminous Curves: C0-C180 Color: C90-C270 Color:

Indoor Budgetary Estimate Table

Lum. Name:55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2023/10/24



Indoor Coefficient of Utilization Table

Lum. Name:55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2023/10/24

Coefficients of Utilization – Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC (%)	80				70				50			30			10			0
RhoW (%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	112	110	108	112	110	108	106	106	104	103	102	101	100	99	98	97	95
2	110	106	102	99	108	104	101	98	101	98	96	98	96	94	95	94	92	91
3	106	100	96	93	104	99	95	92	96	93	90	94	91	89	92	90	88	86
4	102	95	91	87	100	94	90	87	92	89	86	90	87	85	88	86	84	82
5	98	91	86	83	96	90	86	82	88	85	82	87	84	81	85	83	80	79
6	94	87	82	79	93	86	82	79	85	81	78	84	80	78	83	80	77	76
7	91	84	79	76	90	83	79	75	82	78	75	81	77	75	80	77	74	73
8	88	81	76	73	87	80	76	73	79	75	72	78	75	72	78	74	72	71
9	86	78	73	70	85	78	73	70	77	73	70	76	72	70	75	72	70	68
10	83	76	71	68	82	75	71	68	75	71	68	74	70	68	73	70	67	66

Unified Glare Rating Table

Lum. Name:55252	Lum. Catelog:	Test ID:
Lamp Name:	Lamp Catelog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2023/10/24

Unified Glare Rating Table

Ceiling RCC		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
Wall RW		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Floor RFC		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room Size		Vewed crosswise					Vewed endwise				
X=2H	Y=2H	19.6	20.6	20.0	20.9	21.2	19.5	20.5	19.9	20.8	21.1
	Y=3H	19.6	20.5	20.0	20.8	21.2	19.5	20.3	19.8	20.7	21.0
	Y=4H	19.5	20.3	19.9	20.7	21.1	19.4	20.2	19.8	20.5	20.9
	Y=6H	19.4	20.1	19.8	20.5	20.9	19.3	20.0	19.7	20.4	20.8
	Y=8H	19.3	20.0	19.8	20.4	20.8	19.2	19.9	19.6	20.3	20.7
	Y=12H	19.3	19.9	19.7	20.3	20.8	19.1	19.8	19.6	20.2	20.6
X=4H	Y=2H	19.7	20.5	20.1	20.8	21.2	19.5	20.3	19.9	20.6	21.0
	Y=3H	19.7	20.4	20.1	20.8	21.2	19.4	20.1	19.9	20.5	20.9
	Y=4H	19.6	20.2	20.0	20.6	21.0	19.3	19.9	19.8	20.3	20.8
	Y=6H	19.5	20.0	19.9	20.4	20.9	19.2	19.7	19.7	20.2	20.6
	Y=8H	19.4	19.9	19.9	20.3	20.8	19.1	19.6	19.6	20.1	20.5
	Y=12H	19.3	19.7	19.8	20.2	20.7	19.1	19.5	19.6	20.0	20.4
X=8H	Y=4H	19.4	19.9	19.9	20.3	20.8	19.1	19.6	19.6	20.1	20.5
	Y=6H	19.3	19.7	19.8	20.2	20.7	19.0	19.4	19.5	19.9	20.4
	Y=8H	19.2	19.5	19.8	20.1	20.6	18.9	19.3	19.5	19.8	20.3
	Y=12H	19.2	19.4	19.7	19.9	20.5	18.9	19.2	19.4	19.7	20.3
X=12H	Y=4H	19.4	19.8	19.8	20.2	20.7	19.1	19.5	19.6	20.0	20.4
	Y=6H	19.2	19.5	19.8	20.0	20.6	19.0	19.3	19.5	19.7	20.3
	Y=8H	19.2	19.4	19.7	19.9	20.5	18.9	19.2	19.4	19.7	20.3
Variations with the objverver position at spacings											
S=1.0H		0.0/0.0					0.0/0.0				
S=1.5H		6.3/0.0					9.9/0.0				
S=2.0H		5.2/0.0					6.6/0.0				
Reduced UGR Table:											
Nordic Standard Table:		BK0					BK0				
Correction Value		0.3					0.2				

o the CIE Pub.117, data has been corrected, refers to the lamp's lumens 8.2flm.

IES Indoor Report

Photometric Filename:FL-10W-COB-1000-1H-15度.IES

Candela Tabulation

V/H	C0. 0	C30. 0	C60. 0	C90. 0	C120. 0	C150. 0	C180. 0	C210. 0	C240. 0	C270. 0	C300. 0	C330. 0
γ 0. 0	6116. 13	6116. 13	6116. 13	6116. 13	6116. 13	6116. 13	6116. 13	6116. 13	6116. 13	6116. 13	6116. 13	6116. 13
γ 1. 0	5818. 35	5988. 69	6004. 93	6046. 67	5927. 75	5897. 63	6188. 15	6216. 54	6232. 42	6215. 19	6195. 75	6157. 69
γ 2. 0	5448. 06	5693. 47	5697. 85	5789. 62	5643. 80	5595. 93	6206. 06	6141. 74	6144. 97	6092. 50	6124. 61	6100. 23
γ 3. 0	4972. 66	5290. 06	5300. 46	5415. 87	5212. 96	5179. 79	6081. 80	5958. 50	5949. 96	5852. 74	5926. 77	5922. 51
γ 4. 0	4347. 59	4753. 53	4763. 56	4913. 78	4703. 13	4644. 03	5855. 32	5639. 42	5619. 34	5509. 31	5627. 08	5639. 13
γ 5. 0	3679. 84	4117. 81	4132. 09	4322. 34	4076. 94	4014. 70	5511. 16	5218. 89	5200. 19	5035. 04	5199. 70	5234. 89
γ 6. 0	2998. 44	3428. 48	3467. 03	3683. 67	3416. 68	3356. 31	5028. 08	4667. 94	4639. 98	4458. 76	4661. 13	4692. 18
γ 7. 0	2379. 45	2762. 66	2790. 45	3006. 67	2756. 15	2704. 01	4458. 38	4052. 17	4018. 48	3820. 86	4027. 02	4063. 04
γ 8. 0	1868. 67	2174. 41	2198. 65	2388. 57	2184. 98	2131. 80	3815. 63	3398. 35	3370. 51	3143. 02	3354. 41	3389. 00
γ 9. 0	1521. 17	1723. 45	1726. 06	1867. 41	1717. 42	1687. 71	3150. 42	2758. 87	2723. 92	2520. 36	2717. 79	2728. 15
γ 10. 0	1277. 54	1417. 44	1418. 89	1500. 46	1402. 46	1383. 91	2539. 47	2184. 75	2148. 70	1982. 07	2150. 61	2156. 54
γ 11. 0	1106. 24	1204. 59	1204. 45	1259. 01	1185. 47	1172. 01	1998. 27	1732. 86	1707. 05	1603. 71	1707. 88	1714. 91
γ 12. 0	983. 34	1054. 24	1050. 20	1086. 41	1037. 55	1032. 19	1599. 86	1431. 77	1420. 07	1345. 01	1411. 06	1416. 17
γ 13. 0	893. 54	946. 17	942. 01	969. 74	940. 15	939. 30	1329. 71	1215. 37	1215. 94	1157. 57	1201. 09	1201. 82
γ 14. 0	821. 53	863. 94	859. 53	885. 11	865. 25	865. 22	1137. 97	1061. 82	1065. 84	1024. 18	1052. 35	1049. 04
γ 15. 0	757. 52	794. 98	789. 71	814. 00	798. 20	799. 22	1010. 07	956. 41	957. 14	925. 54	947. 41	941. 41
γ 16. 0	696. 52	731. 91	726. 16	749. 69	735. 27	736. 16	920. 60	875. 78	872. 35	847. 09	866. 31	861. 90
γ 17. 0	636. 55	670. 64	664. 83	687. 79	673. 58	674. 36	848. 68	805. 43	800. 83	779. 13	797. 64	794. 59
γ 18. 0	579. 03	611. 34	605. 18	627. 59	613. 81	613. 82	781. 38	740. 03	734. 54	714. 15	733. 72	731. 10
γ 19. 0	523. 33	553. 86	547. 32	569. 28	555. 09	555. 43	717. 81	677. 26	671. 99	652. 93	672. 23	669. 80
γ 20. 0	470. 85	497. 92	491. 75	512. 83	499. 55	499. 98	656. 44	616. 74	612. 63	594. 36	613. 35	610. 88
γ 21. 0	423. 25	446. 74	440. 56	459. 89	448. 25	450. 50	596. 63	558. 11	554. 58	537. 26	556. 19	554. 43
γ 22. 0	381. 98	401. 65	396. 40	412. 35	403. 92	406. 28	538. 84	503. 31	499. 96	483. 83	501. 86	500. 34
γ 23. 0	344. 00	362. 04	357. 76	371. 85	363. 62	365. 86	484. 64	453. 95	451. 05	435. 62	452. 19	450. 70
γ 24. 0	310. 13	326. 37	323. 67	335. 45	327. 56	329. 22	435. 95	410. 21	407. 74	394. 31	408. 42	406. 04
γ 25. 0	280. 17	295. 20	293. 12	303. 57	295. 86	296. 95	393. 54	371. 36	369. 58	356. 59	369. 64	366. 06
γ 26. 0	253. 49	267. 77	266. 35	275. 70	268. 33	268. 81	355. 09	335. 78	334. 77	322. 51	334. 35	329. 76
γ 27. 0	229. 76	243. 32	242. 59	250. 76	243. 88	243. 67	320. 59	304. 19	303. 58	292. 65	302. 45	298. 06
γ 28. 0	208. 84	221. 30	221. 22	227. 91	221. 76	221. 17	289. 94	276. 50	275. 70	265. 70	274. 32	269. 58
γ 29. 0	190. 72	202. 14	202. 36	207. 96	202. 58	202. 26	262. 98	251. 54	250. 93	241. 92	249. 05	243. 91
γ 30. 0	173. 78	185. 27	185. 78	191. 07	185. 20	184. 85	238. 20	229. 11	228. 70	220. 24	226. 15	220. 80
γ 31. 0	158. 40	169. 83	170. 45	175. 46	168. 81	168. 29	216. 33	209. 38	209. 19	200. 85	206. 63	201. 12
γ 32. 0	144. 11	154. 68	155. 43	160. 38	153. 74	153. 22	198. 26	192. 13	192. 03	184. 24	188. 73	183. 22
γ 33. 0	131. 78	141. 33	142. 47	146. 62	140. 76	140. 04	180. 93	175. 76	176. 40	167. 95	172. 35	166. 51
γ 34. 0	120. 75	129. 79	131. 11	134. 62	129. 65	128. 44	164. 79	160. 19	160. 98	153. 23	156. 95	151. 35
γ 35. 0	111. 26	119. 61	120. 89	123. 99	119. 60	118. 25	150. 29	146. 63	147. 33	140. 63	143. 37	137. 88
γ 36. 0	102. 65	110. 57	111. 75	114. 50	110. 57	109. 46	137. 76	134. 93	135. 47	129. 43	131. 35	125. 96
γ 37. 0	94. 86	102. 21	103. 46	106. 01	102. 40	101. 11	126. 74	124. 43	125. 01	119. 65	120. 77	115. 86
γ 38. 0	87. 96	94. 54	95. 82	98. 33	94. 87	93. 73	116. 91	114. 97	115. 49	110. 73	111. 46	106. 90
γ 39. 0	81. 56	87. 50	89. 00	91. 51	87. 96	86. 83	108. 02	106. 59	106. 74	102. 39	102. 99	98. 75
γ 40. 0	76. 09	81. 17	82. 74	85. 09	81. 77	80. 55	100. 04	98. 95	98. 75	94. 72	95. 27	91. 48
γ 41. 0	71. 22	75. 71	77. 28	79. 18	76. 34	75. 30	92. 63	91. 90	91. 56	87. 79	88. 26	84. 79
γ 42. 0	66. 72	70. 69	71. 97	74. 01	71. 32	70. 46	85. 82	85. 30	84. 89	81. 75	81. 93	78. 68
γ 43. 0	62. 60	66. 18	67. 36	69. 33	67. 03	66. 11	79. 90	79. 49	79. 19	76. 42	76. 76	73. 66
γ 44. 0	58. 85	62. 07	63. 20	65. 24	62. 65	61. 83	74. 78	74. 12	73. 98	71. 32	71. 75	68. 96
γ 45. 0	55. 49	58. 53	59. 38	61. 23	58. 49	57. 91	69. 90	69. 26	69. 05	66. 76	67. 25	64. 54
γ 46. 0	52. 07	55. 07	55. 67	57. 18	54. 15	53. 50	65. 51	65. 16	64. 78	62. 93	63. 09	60. 71

Photometric Filename:FL-10W-COB-1000-1H-15度.IES

Candela Tabulation - (Cont.)

V/H	C0.0	C30.0	C60.0	C90.0	C120.0	C150.0	C180.0	C210.0	C240.0	C270.0	C300.0	C330.0
γ 47.0	48.46	51.37	51.83	53.01	49.95	49.18	61.10	60.97	60.70	59.26	59.53	57.29
γ 48.0	45.15	47.92	48.11	48.93	46.02	45.42	56.76	56.56	56.69	55.24	55.89	54.11
γ 49.0	41.96	44.58	44.75	45.17	42.51	41.91	52.16	52.12	52.76	51.52	51.90	50.43
γ 50.0	39.05	41.58	41.49	41.90	39.44	38.93	47.98	47.94	49.04	47.68	48.29	46.90
γ 51.0	36.32	38.66	38.50	38.78	36.57	36.04	44.33	44.11	45.32	44.21	45.03	43.57
γ 52.0	33.69	35.84	35.62	36.00	33.79	33.40	41.01	40.80	42.05	41.06	41.82	40.52
γ 53.0	31.21	33.17	32.98	33.37	31.46	30.97	38.12	37.79	38.78	38.02	38.83	37.56
γ 54.0	29.01	30.82	30.68	30.97	29.31	28.87	35.38	35.10	35.79	35.31	35.90	34.87
γ 55.0	26.71	28.44	28.37	28.60	27.04	26.49	32.82	32.42	33.22	32.82	33.26	32.37
γ 56.0	24.28	26.07	26.09	26.37	24.72	24.38	30.54	30.01	30.50	30.25	30.90	30.13
γ 57.0	22.18	23.76	23.95	24.28	22.67	22.35	28.27	27.62	28.09	27.83	28.50	27.84
γ 58.0	20.13	21.76	21.91	22.30	20.79	20.46	26.13	25.30	25.65	25.48	26.10	25.50
γ 59.0	18.28	19.78	20.08	20.36	18.95	18.56	23.92	23.22	23.45	23.09	23.97	23.50
γ 60.0	16.59	17.91	18.21	18.66	17.20	16.90	21.94	21.17	21.45	21.05	21.90	21.49
γ 61.0	14.95	16.18	16.45	16.84	15.53	15.14	20.00	19.29	19.49	19.13	20.02	19.62
γ 62.0	13.36	14.54	14.80	15.20	13.94	13.63	18.25	17.45	17.65	17.33	18.19	17.89
γ 63.0	11.81	13.09	13.32	13.77	12.35	12.18	16.54	15.74	15.89	15.60	16.50	16.25
γ 64.0	10.51	11.57	11.92	12.19	10.95	10.64	14.97	14.20	14.28	14.10	14.86	14.65
γ 65.0	9.15	10.10	10.57	10.78	9.54	9.37	13.47	12.68	12.83	12.59	13.33	13.12
γ 66.0	7.86	8.76	9.10	8.91	8.20	7.93	12.03	11.29	11.29	11.06	11.90	11.70
γ 67.0	6.62	7.45	7.18	6.53	6.83	6.70	10.64	9.89	9.92	9.57	10.49	10.32
γ 68.0	5.39	6.16	3.75	4.55	5.52	5.45	9.25	8.59	8.63	8.22	9.06	8.99
γ 69.0	4.22	5.03	1.19	3.00	4.34	4.30	7.97	7.32	7.19	6.97	7.70	7.66
γ 70.0	3.13	3.66	0.00	1.87	3.16	3.09	6.70	6.04	5.93	5.67	6.39	6.47
γ 71.0	1.96	2.48	0.00	0.73	1.94	1.83	5.46	4.80	4.72	4.52	5.20	5.27
γ 72.0	0.80	1.27	0.00	0.00	0.58	0.43	4.22	3.61	3.50	3.33	3.95	4.10
γ 73.0	0.00	0.11	0.00	0.00	0.00	0.00	3.01	2.33	2.38	2.18	2.72	2.90
γ 74.0	0.00	0.00	0.00	0.00	0.00	0.00	1.70	0.95	1.06	1.03	1.63	1.78
γ 75.0	0.00	0.00	0.00	0.00	0.00	0.00	0.25	0.00	0.00	0.00	0.32	0.43
γ 76.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
γ 77.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
γ 78.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
γ 79.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
γ 80.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
γ 81.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
γ 82.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
γ 83.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
γ 84.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
γ 85.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
γ 86.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
γ 87.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
γ 88.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
γ 89.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
γ 90.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
γ 91.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
γ 92.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
γ 93.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Photometric Filename:FL-10W-COB-1000-1H-15度.IES[illegible]

Photometric Filename:FL-10W-COB-1000-1H-15度.IES

[illegible]