



Indoor Luminaire Photometric Data

Description Information

Luminary Name: 55252		Lum. Catalog:	Test ID:
Lamp Name:		Lamp Catalog:	Test Date: 2024/05/10
Manufacture:		Shld. Ang(°):	Test Machine:GON-2000
Test Lab:		Frequency (Hz):	Lamp CCT(K): 3000 Ra:
Lum. Size(W*L*H):0.045m*1.000m*0.044m		Lum. Area(m2):0.089	Lum. W(kg): 0.000
Test System: C, γ	Test Step: C=30.0 γ=1.0	Temp. (°C): 25	Humidity(%): 50.0


Character Parameter

Lamp Speciality Parameter		Luminaire Speciality Parameter	
Rated Flux(lm): 425.860	Luminary Flux(lm): 425.859	Field Angle(10%Imax): 63.7(°)	
Rated Power(W): 10	Luminary Efficiency: 100.00%	Down Lumens&Percent: 425.858lm 100.00%	
Rated Voltage(V): 220	Luminary EER(lm/W): 44.259	Up Lumens&Percent: 0.001lm 0.00%	
Tested Power(W): 9.622	Max. Candela(cd): 980.904	S/MH: C0_a180=0.588 C90_270=0.607	
Lamps' Inside: 1	Max Cand@Ang. (°): C=240.0 γ=9.0	CIE Type: Semi-Direct	
Tested Electrics(V, A, pf):222.9, 0.050, 0.861	Beam Angle(50%Imax): 34.5(°)	ErP Φuse(90°): 421.108lm	
Lamp Size(W*L*H):0.045m*1.000m*0.044m	Left=-8.6°, Right=25.9°	IRF(%): 537.583	



2D Plane Light Intensity Distribution Curve


Lum. Name:55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date:2024/05/10



3D Light Intensity Distribution Modal

Lum. Name:55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2024/05/10

3D Light Intensity Distribution Modal



Curves:

View Angles:

3D Model

Orient:0

Fixture

Tilt:0

Vert. HUD

Roll:0

Hori. HUD

Spin:0

Photometric Filename:FL-8001-1000-IH-30度透镜带防眩罩-黑.IES

Zone(γ)	Zone Flux (1m)	Sums Flux (1m)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (1m)	Sums Flux (1m)	Zone%Lamp	Sums%Lamp
0.0-1.0	0.83	0.83	0.19	0.19	47.0-48.0	1.10	420.95	0.26	98.85
1.0-2.0	2.47	3.30	0.58	0.78	48.0-49.0	0.95	421.89	0.22	99.07
2.0-3.0	4.09	7.39	0.96	1.73	49.0-50.0	0.81	422.71	0.19	99.26
3.0-4.0	5.65	13.04	1.33	3.06	50.0-51.0	0.69	423.40	0.16	99.42
4.0-5.0	7.15	20.19	1.68	4.74	51.0-52.0	0.58	423.98	0.14	99.56
5.0-6.0	8.57	28.76	2.01	6.75	52.0-53.0	0.48	424.45	0.11	99.67
6.0-7.0	9.90	38.66	2.32	9.08	53.0-54.0	0.39	424.84	0.09	99.76
7.0-8.0	11.12	49.78	2.61	11.69	54.0-55.0	0.31	425.15	0.07	99.83
8.0-9.0	12.22	62.00	2.87	14.56	55.0-56.0	0.24	425.38	0.06	99.89
9.0-10.0	13.20	75.20	3.10	17.66	56.0-57.0	0.18	425.56	0.04	99.93
10.0-11.0	14.05	89.24	3.30	20.96	57.0-58.0	0.13	425.69	0.03	99.96
11.0-12.0	14.76	104.00	3.47	24.42	58.0-59.0	0.08	425.77	0.02	99.98
12.0-13.0	15.34	119.34	3.60	28.02	59.0-60.0	0.05	425.82	0.01	99.99
13.0-14.0	15.77	135.11	3.70	31.73	60.0-61.0	0.03	425.85	0.01	100.00
14.0-15.0	16.06	151.17	3.77	35.50	61.0-62.0	0.01	425.86	0.00	100.00
15.0-16.0	16.21	167.39	3.81	39.31	62.0-63.0	0.00	425.86	0.00	100.00
16.0-17.0	16.22	183.61	3.81	43.12	63.0-64.0	0.00	425.86	0.00	100.00
17.0-18.0	16.10	199.71	3.78	46.90	64.0-65.0	0.00	425.86	0.00	100.00
18.0-19.0	15.86	215.57	3.72	50.62	65.0-66.0	0.00	425.86	0.00	100.00
19.0-20.0	15.51	231.08	3.64	54.26	66.0-67.0	0.00	425.86	0.00	100.00
20.0-21.0	15.05	246.14	3.54	57.80	67.0-68.0	0.00	425.86	0.00	100.00
21.0-22.0	14.52	260.65	3.41	61.21	68.0-69.0	0.00	425.86	0.00	100.00
22.0-23.0	13.91	274.57	3.27	64.47	69.0-70.0	0.00	425.86	0.00	100.00
23.0-24.0	13.25	287.81	3.11	67.58	70.0-71.0	0.00	425.86	0.00	100.00
24.0-25.0	12.54	300.35	2.94	70.53	71.0-72.0	0.00	425.86	0.00	100.00
25.0-26.0	11.81	312.16	2.77	73.30	72.0-73.0	0.00	425.86	0.00	100.00
26.0-27.0	11.06	323.22	2.60	75.90	73.0-74.0	0.00	425.86	0.00	100.00
27.0-28.0	10.30	333.52	2.42	78.32	74.0-75.0	0.00	425.86	0.00	100.00
28.0-29.0	9.55	343.06	2.24	80.56	75.0-76.0	0.00	425.86	0.00	100.00
29.0-30.0	8.81	351.87	2.07	82.63	76.0-77.0	0.00	425.86	0.00	100.00
30.0-31.0	8.09	359.96	1.90	84.53	77.0-78.0	0.00	425.86	0.00	100.00
31.0-32.0	7.41	367.36	1.74	86.26	78.0-79.0	0.00	425.86	0.00	100.00
32.0-33.0	6.75	374.11	1.58	87.85	79.0-80.0	0.00	425.86	0.00	100.00
33.0-34.0	6.12	380.24	1.44	89.29	80.0-81.0	0.00	425.86	0.00	100.00
34.0-35.0	5.53	385.77	1.30	90.59	81.0-82.0	0.00	425.86	0.00	100.00
35.0-36.0	4.98	390.75	1.17	91.76	82.0-83.0	0.00	425.86	0.00	100.00
36.0-37.0	4.47								

IES Indoor Report


Photometric Filename:FL-8001-1000-IH-30度透镜带防眩罩-黑.IES

Zonal Flux Tabulation - (Cont.)

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
94.0-95.0	0.00	425.86	0.00	100.00	141.0-142.0	0.00	425.86	0.00	100.00
95.0-96.0	0.00	425.86	0.00	100.00	142.0-143.0	0.00	425.86	0.00	100.00
96.0-97.0	0.00	425.86	0.00	100.00	143.0-144.0	0.00	425.86	0.00	100.00
97.0-98.0	0.00	425.86	0.00	100.00	144.0-145.0	0.00	425.86	0.00	100.00
98.0-99.0	0.00	425.86	0.00	100.00	145.0-146.0	0.00	425.86	0.00	100.00
99.0-100.0	0.00	425.86	0.00	100.00	146.0-147.0	0.00	425.86	0.00	100.00
100.0-101.0	0.00	425.86	0.00	100.00	147.0-148.0	0.00	425.86	0.00	100.00
101.0-102.0	0.00	425.86	0.00	100.00	148.0-149.0	0.00	425.86	0.00	100.00
102.0-103.0	0.00	425.86	0.00	100.00	149.0-150.0	0.00	425.86	0.00	100.00
103.0-104.0	0.00	425.86	0.00	100.00	150.0-151.0	0.00	425.86	0.00	100.00
104.0-105.0	0.00	425.86	0.00	100.00	151.0-152.0	0.00	425.86	0.00	100.00
105.0-106.0	0.00	425.86	0.00	100.00	152.0-153.0	0.00	425.86	0.00	100.00
106.0-107.0	0.00	425.86	0.00	100.00	153.0-154.0	0.00	425.86	0.00	100.00
107.0-108.0	0.00	425.86	0.00	100.00	154.0-155.0	0.00	425.86	0.00	100.00
108.0-109.0	0.00	425.86	0.00	100.00	155.0-156.0	0.00	425.86	0.00	100.00
109.0-110.0	0.00	425.86	0.00	100.00	156.0-157.0	0.00	425.86	0.00	100.00
110.0-111.0	0.00	425.86	0.00	100.00	157.0-158.0	0.00	425.86	0.00	100.00
111.0-112.0	0.00	425.86	0.00	100.00	158.0-159.0	0.00	425.86	0.00	100.00
112.0-113.0	0.00	425.86	0.00	100.00	159.0-160.0	0.00	425.86	0.00	100.00
113.0-114.0	0.00	425.86	0.00	100.00	160.0-161.0	0.00	425.86	0.00	100.00
114.0-115.0	0.00	425.86	0.00	100.00	161.0-162.0	0.00	425.86	0.00	100.00
115.0-116.0	0.00	425.86	0.00	100.00	162.0-163.0	0.00	425.86	0.00	100.00
116.0-117.0	0.00	425.86	0.00	100.00	163.0-164.0	0.00	425.86	0.00	100.00
117.0-118.0	0.00	425.86	0.00	100.00	164.0-165.0	0.00	425.86	0.00	100.00
118.0-119.0	0.00	425.86	0.00	100.00	165.0-166.0	0.00	425.86	0.00	100.00
119.0-120.0	0.00	425.86	0.00	100.00	166.0-167.0	0.00	425.86	0.00	100.00
120.0-121.0	0.00	425.86	0.00	100.00	167.0-168.0	0.00	425.86	0.00	100.00
121.0-122.0	0.00	425.86	0.00	100.00	168.0-169.0	0.00	425.86	0.00	100.00
122.0-123.0	0.00	425.86	0.00	100.00	169.0-170.0	0.00	425.86	0.00	100.00
123.0-124.0	0.00	425.86	0.00	100.00	170.0-171.0	0.00	425.86	0.00	100.00
124.0-125.0	0.00	425.86	0.00	100.00	171.0-172.0	0.00	425.86	0.00	100.00
125.0-126.0	0.00	425.86	0.00	100.00	172.0-173.0	0.00	425.86	0.00	100.00
126.0-127.0	0.00	425.86	0.00	100.00	173.0-174.0	0.00	425.86	0.00	100.00
127.0-128.0	0.00	425.86	0.00	100.00	174.0-175.0	0.00	425.86	0.00	100.00
128.0-129.0	0.00	425.86	0.00	100.00	175.0-176.0	0.00	425.86	0.00	100.00
129.0-130.0	0.00	425.86	0.00	100.00	176.0-177.0	0.00	425.86	0.00	100.00
130.0-131.0	0.00	425.86	0.00	100.00	177.0-178.0	0.00	425.86	0.00	100.00
131.0-132.0	0.00	425.86	0.00	100.00	178.0-179.0	0.00	425.86	0.00	100.00
132.0-133.0	0.00	425.86	0.00	100.00	179.0-180.0	0.00	425.86	0.00	100.00
133.0-134.0	0.00	425.86	0.00	100.00					
134.0-135.0	0.00	425.86	0.00	100.00					
135.0-136.0	0.00	425.86	0.00	100.00					
136.0-137.0	0.00	425.86	0.00	100.00					
137.0-138.0	0.00	425.86	0.00	100.00					
138.0-139.0	0.00	425.86	0.00	100.00					
139.0-140.0	0.00	425.86	0.00	100.00					
140.0-141.0	0.00	425.86	0.00	100.00					

Rectangle ISO Lighting Intensity Diagram

Lum. Name: 55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2024/05/10



Maximum Light Intensity(cd): 980.90


Maximum Cand.@Angle: H=-4.5°,V=-7.8°

Photometric Filename:FL-8001-1000-IH-30度透镜带防眩罩-黑.IES

Plane ISO-Illuminance Diagram

Lum. Name: 55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2024/05/10

Plane ISO-Illuminance Curve



Working Plane Luminaire Mounting Height(m): 3.00


Working Plane Maximum Illuminance(lx): 105.90

Working Plane Maximum Illuminance Position(d/h):H-0.1 V-0.1

3D Plane ISO Illuminance Diagram

Lum. Name: 55252	Lum. Catelog:	Test ID:
Lamp Name:	Lamp Catelog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2024/05/10


3D Plane Illuminance Modal



Space ISO Illuminance Diagram

Lum. Name: 55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2024/05/10


Space ISO Illuminance Curve



Space Plane Maximum Illuminance and @Angle:876.44lx,1.0deg
Plane Maximum Lighting Intensity and @Angle:876.842cd,0deg

Illuminance-Distance Diagram

Lum. Name:55252	Lum. Catelog:	Test ID:
Lamp Name:	Lamp Catelog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2024/05/10



Indoor Luminance Limiting Curves

Lum. Name:55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2024/05/10


Glare Grade Table

GI	Quality	Using Illuminance							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama (deg)	45	50	55	60	65	70	75	80	85
C0	38	0	0	0	0	0	0	0	0
C90	1	0	0	0	0	0	0	0	0

Luminance Limiting Curve



Luminous Size:

Length(m)=1.000

Width(m)=0.045

Height(m)=0.044

Area(m^2)=0.089000

Luminous Type:

Without Luminous Side


Luminous Curves:

C0-C180 Color:

C90-C270 Color:

Indoor Budgetary Estimate Table

Lum. Name: 55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2024/05/10



Indoor Coefficient of Utilization Table

Lum. Name:55252	Lum. Catelog:	Test ID:
Lamp Name:	Lamp Catelog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2024/05/10

Coefficients of Utilization – Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC (%)	80				70				50			30			10			0
RhoW (%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	112	109	107	112	109	107	106	105	104	102	102	101	99	98	97	97	95
2	109	105	101	98	107	103	100	97	100	97	95	97	95	93	94	93	91	90
3	105	99	94	91	103	97	93	90	95	92	89	93	90	87	90	88	86	85
4	100	93	89	85	98	92	88	84	90	86	83	88	85	82	86	84	81	80
5	96	88	83	80	94	88	83	79	86	82	78	84	81	78	83	80	77	76
6	92	84	79	75	90	83	78	75	82	77	74	80	77	74	79	76	73	72
7	88	80	75	71	87	79	74	71	78	74	70	77	73	70	76	72	70	68
8	85	76	71	67	83	76	71	67	75	70	67	74	70	67	73	69	66	65
9	81	73	67	64	80	72	67	64	71	67	64	71	66	63	70	66	63	62
10	78	70	64	61	77	69	64	61	68	64	61	68	64	61	67	63	60	59

Unified Glare Rating Table

Lum. Name:55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date:2024/05/10

Unified Glare Rating Table

Ceiling RCC		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
Wall RW		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Floor RFC		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room Size		Vewed crosswise					Vewed endwise				
X=2H	Y=2H	0.3	1.2	0.6	1.5	1.8	-8.9	-8.0	-8.6	-7.7	-7.4
	Y=3H	0.1	0.9	0.4	1.2	1.6	-9.1	-8.3	-8.8	-8.0	-7.6
	Y=4H	-0.0	0.7	0.4	1.0	1.4	-9.3	-8.5	-8.8	-8.2	-7.8
	Y=6H	-0.2	0.5	0.3	0.9	1.3	-9.4	-8.7	-8.9	-8.3	-7.9
	Y=8H	-0.2	0.4	0.2	0.8	1.2	-9.4	-8.8	-9.0	-8.4	-8.0
	Y=12H	-0.3	0.3	0.2	0.7	1.1	-9.5	-8.9	-9.1	-8.5	-8.1
X=4H	Y=2H	-0.0	0.7	0.4	1.1	1.5	-9.3	-8.5	-8.8	-8.2	-7.8
	Y=3H	-0.2	0.4	0.2	0.8	1.2	-9.5	-8.9	-9.1	-8.5	-8.1
	Y=4H	-0.4	0.2	0.1	0.6	1.0	-9.6	-9.1	-9.2	-8.7	-8.2
	Y=6H	-0.5	-0.0	-0.0	0.4	0.9	-9.7	-9.3	-9.2	-8.8	-8.3
	Y=8H	-0.6	-0.1	-0.1	0.3	0.8	-9.8	-9.4	-9.3	-8.9	-8.5
	Y=12H	-0.6	-0.3	-0.1	0.2	0.7	-9.9	-9.5	-9.4	-9.0	-8.5
X=8H	Y=4H	-0.6	-0.1	-0.1	0.3	0.8	-9.8	-9.4	-9.3	-8.9	-8.5
	Y=6H	-0.7	-0.4	-0.2	0.1	0.6	-9.9	-9.6	-9.4	-9.1	-8.6
	Y=8H	-0.8	-0.5	-0.2	0.0	0.5	-10.0	-9.7	-9.5	-9.2	-8.7
	Y=12H	-0.8	-0.6	-0.3	-0.1	0.5	-10.1	-9.8	-9.5	-9.3	-8.7
X=12H	Y=4H	-0.6	-0.3	-0.1	0.2	0.7	-9.9	-9.5	-9.4	-9.0	-8.5
	Y=6H	-0.8	-0.5	-0.2	-0.0	0.5	-10.0	-9.7	-9.5	-9.2	-8.7
	Y=8H	-0.8	-0.6	-0.3	-0.1	0.5	-10.1	-9.8	-9.5	-9.3	-8.7
Variations with the objerver position at spacings											
S=1.0H		0.0/0.0					0.0/0.0				
S=1.5H		0.0/0.0					0.0/0.0				
S=2.0H		0.0/0.0					0.0/0.0				
Reduced UGR Table:											
Nordic Standard Table:		BK0					BK0				
Correction Value		0.0					0.0				

o the CIE Pub.117, data has been corrected, refers to the lamp's lumens 8.2flm.

Candela Tabulation

V/H	C0. 0	C30. 0	C60. 0	C90. 0	C120. 0	C150. 0	C180. 0	C210. 0	C240. 0	C270. 0	C300. 0	C330. 0
γ 0. 0	870. 32	870. 32	870. 32	870. 32	870. 32	870. 32	870. 32	870. 32	870. 32	870. 32	870. 32	870. 32
γ 1. 0	876. 84	818. 80	797. 53	815. 27	837. 04	886. 07	913. 31	878. 35	862. 74	875. 03	887. 75	917. 60
γ 2. 0	852. 66	784. 39	760. 60	779. 74	806. 44	864. 24	926. 01	902. 99	891. 05	899. 90	907. 21	928. 00
γ 3. 0	824. 60	747. 83	720. 83	741. 84	772. 56	838. 64	935. 14	923. 85	915. 18	921. 40	923. 40	934. 65
γ 4. 0	792. 94	708. 51	679. 37	702. 60	735. 79	809. 23	941. 11	940. 47	935. 85	939. 75	936. 38	938. 13
γ 5. 0	758. 75	668. 06	638. 20	662. 38	697. 53	777. 05	943. 20	952. 85	952. 66	954. 34	946. 03	937. 67
γ 6. 0	721. 93	627. 62	596. 55	621. 53	658. 16	742. 00	941. 04	961. 99	965. 97	965. 20	951. 64	932. 62
γ 7. 0	682. 90	586. 34	555. 36	580. 23	617. 61	704. 22	934. 47	966. 89	974. 76	971. 67	953. 00	923. 56
γ 8. 0	642. 51	545. 56	514. 75	539. 11	576. 14	664. 70	923. 90	968. 34	979. 66	974. 25	949. 91	910. 62
γ 9. 0	601. 33	505. 80	474. 17	498. 08	535. 04	624. 08	908. 97	965. 68	980. 90	972. 96	942. 70	893. 24
γ 10. 0	559. 72	467. 77	435. 16	457. 85	494. 68	582. 61	890. 22	958. 98	978. 16	967. 62	931. 07	872. 08
γ 11. 0	518. 29	431. 06	398. 91	419. 42	455. 32	540. 98	867. 47	947. 68	971. 71	957. 88	916. 08	847. 19
γ 12. 0	478. 06	395. 02	364. 03	383. 32	416. 59	500. 24	841. 17	932. 35	960. 86	943. 92	896. 78	818. 52
γ 13. 0	438. 95	360. 96	330. 03	348. 36	380. 11	460. 87	811. 21	913. 83	946. 32	926. 52	873. 27	786. 35
γ 14. 0	401. 21	327. 73	297. 80	315. 50	345. 66	422. 12	777. 87	891. 27	927. 54	905. 07	845. 96	751. 26
γ 15. 0	365. 80	295. 78	267. 99	284. 49	312. 91	385. 40	740. 87	865. 69	905. 29	879. 97	815. 05	713. 35
γ 16. 0	330. 87	265. 73	239. 72	254. 88	281. 19	350. 15	702. 24	837. 19	879. 36	850. 03	780. 48	674. 26
γ 17. 0	297. 03	238. 11	213. 53	227. 18	251. 58	315. 90	663. 08	804. 69	849. 85	816. 34	743. 86	634. 17
γ 18. 0	265. 09	213. 28	190. 21	202. 27	223. 90	282. 93	622. 11	769. 80	816. 82	779. 92	704. 63	593. 40
γ 19. 0	235. 88	190. 63	169. 20	179. 47	197. 54	252. 26	580. 42	732. 20	780. 59	741. 23	663. 78	552. 59
γ 20. 0	208. 91	169. 62	150. 13	158. 80	173. 69	223. 76	539. 20	692. 33	741. 20	700. 04	621. 87	512. 54
γ 21. 0	183. 98	150. 61	132. 67	140. 02	152. 43	197. 61	498. 38	650. 71	699. 86	657. 39	579. 27	473. 01
γ 22. 0	159. 92	133. 48	117. 01	123. 55	134. 21	173. 48	459. 50	608. 17	657. 41	614. 38	537. 33	434. 86
γ 23. 0	136. 67	117. 83	102. 77	108. 77	117. 02	149. 77	422. 16	565. 66	614. 72	571. 90	496. 43	398. 85
γ 24. 0	116. 85	103. 76	90. 07	95. 19	100. 29	128. 11	386. 95	524. 01	571. 61	529. 77	456. 87	364. 30
γ 25. 0	100. 27	90. 65	78. 01	82. 88	85. 31	109. 40	353. 46	482. 46	528. 53	487. 93	419. 55	332. 34
γ 26. 0	85. 89	78. 95	67. 69	71. 93	72. 52	93. 93	321. 39	441. 21	485. 48	447. 49	384. 23	301. 14
γ 27. 0	73. 12	68. 59	58. 80	62. 20	61. 39	80. 39	290. 38	401. 22	444. 61	409. 10	349. 54	271. 36
γ 28. 0	61. 19	59. 58	50. 86	53. 97	51. 66	68. 16	261. 55	363. 86	405. 90	372. 93	317. 26	243. 72
γ 29. 0	50. 84	51. 86	43. 94	46. 75	42. 92	56. 84	234. 28	328. 70	368. 97	338. 49	286. 48	218. 04
γ 30. 0	42. 99	44. 66	37. 31	40. 28	35. 51	47. 53	209. 07	295. 91	334. 18	306. 10	257. 71	194. 34
γ 31. 0	36. 89	38. 37	31. 27	34. 43	29. 64	40. 28	186. 24	265. 46	301. 38	275. 55	230. 86	172. 94
γ 32. 0	31. 55	32. 70	26. 17	28. 84	24. 90	34. 49	165. 54	237. 14	270. 71	246. 80	206. 04	153. 70
γ 33. 0	27. 04	27. 79	21. 92	24. 04	21. 03	29. 58	146. 99	210. 57	241. 96	220. 41	182. 99	136. 47
γ 34. 0	23. 09	23. 37	18. 05	19. 88	17. 55	25. 39	129. 94	186. 15	215. 49	195. 88	162. 35	120. 75
γ 35. 0	19. 71	19. 59	14. 66	16. 24	14. 68	21. 59	114. 86	164. 10	191. 08	173. 81	143. 88	106. 33
γ 36. 0	16. 56	16. 27	12. 00	13. 08	12. 22	18. 40	101. 01	144. 31	168. 92	153. 55	127. 20	93. 03
γ 37. 0	13. 97	13. 35	9. 81	10. 48	10. 14	15. 48	88. 44	126. 84	149. 10	136. 00	112. 46	81. 32
γ 38. 0	11. 76	10. 91	7. 89	8. 33	8. 40	12. 98	77. 22	111. 86	131. 62	120. 31	99. 09	70. 92
γ 39. 0	9. 80	8. 68	6. 37	6. 52	6. 76	10. 79	67. 09	98. 70	116. 11	106. 50	86. 82	61. 57
γ 40. 0	8. 16	6. 73	5. 03	4. 84	5. 42	9. 05	58. 54	86. 77	102. 60	93. 59	75. 77	53. 63
γ 41. 0	6. 74	5. 23	3. 88	3. 53	4. 30	7. 45	51. 20	75. 83	90. 26	81. 88	65. 75	46. 63
γ 42. 0	5. 44	3. 90	2. 91	2. 34	3. 33	6. 01	44. 54	66. 06	78. 92	71. 46	57. 32	40. 57
γ 43. 0	4. 33	2. 76	1. 91	1. 44	2. 36	4. 90	38. 71	57. 27	68. 76	62. 17	50. 14	34. 93
γ 44. 0	3. 28	1. 78	0. 99	0. 65	1. 63	3. 81	33. 14	49. 62	59. 69	54. 07	43. 74	30. 00
γ 45. 0	2. 36	0. 96	0. 28	0. 04	0. 93	2. 85	28. 30	43. 19	51. 73	47. 20	37. 94	25. 80
γ 46. 0	1. 66	0. 24	0. 00	0. 00	0. 26	2. 03	24. 28	37. 50	45. 06	41. 08	32. 56	22. 07

Photometric Filename:FL-8001-1000-IH-30度透镜带防眩罩-黑.IES

[illegible]

Photometric Filename:FL-8001-1000-IH-30度透镜带防眩罩-黑.IES

[illegible]

Photometric Filename:FL-8001-1000-IH-30度透镜带防眩罩-黑.IES

[illegible]