




DIN flange-2544-45-46


PN	DN	NPS	A	B	C	T	f	Bolt Hole	
								N	φ
25	15	1/2	95	65	45	16	2	4	14
	20	3/4	105	75	58	18	2	4	14
	25	1	115	85	68	18	2	4	14
	32	1 1/4	140	100	78	18	2	4	18
	40	1 1/2	150	110	88	18	2	4	18
40	50	2	165	125	102	20	2	4	18
	15	1/2	105	75	45	20	2	4	14
	20	3/4	130	90	58	22	2	4	18
	25	1	140	100	65	24	2	4	18
	32	1 1/4	155	110	75	24	2	4	22
64	40	1 1/2	170	125	88	26	2	4	22
	50	2	180	135	95	26	2	4	22





(RF)
150~300LB




(RF)
600~2500LB




(RJ)
600~2500LB



(RF)
PN1.6~4.0MPa



(FM)
PN4.0~16.0MPa



(RJ)
PN6.3~16.0MPa



JB/T79.1~4-94;JB/T82.1~4-94

Unit:mm

Flange standard ASME B16.5

CLASS	NPS	A	B	C	T	Bolt Hole		Ring Type Joint				Ring No.
						N	φ	K	P	F	E	
150	1/2	89	60.3	34.9	11.5	4	16	-	-	-	-	-
	3/4	98	69.8	42.9	13.0	4	16	-	-	-	-	-
	1	108	79.4	50.8	14.5	4	16	63.5	47.62	8.74	6.4	R15
	1 1/4	117	88.9	63.5	16.0	4	16	73.0	57.15	8.74	6.4	R17
	1 1/2	127	98.4	73.0	17.5	4	16	82.5	65.07	8.74	6.4	R19
	2	152	120.6	92.1	19.5	4	20	102.0	82.55	8.74	6.4	R22
300	1/2	95	66.7	34.9	14.5	4	16	51.0	34.14	7.14	5.6	R11
	3/4	117	82.5	42.9	16.0	4	20	63.5	42.88	8.74	6.4	R13
	1	124	88.9	50.8	17.5	4	20	70.0	50.80	8.74	6.4	R16
	1 1/4	133	98.4	63.5	19.5	4	20	79.5	60.32	8.74	6.4	R18
	1 1/2	156	114.3	73.0	21.0	4	23	90.5	68.28	8.74	6.4	R20
	2	165	127.0	92.1	22.5	8	20	108.0	82.55	11.91	8.0	R23
600	1/2	95	66.7	34.9	14.5	4	16	51.0	34.14	7.14	5.6	R11
	3/4	117	82.5	42.9	16.0	4	20	63.5	42.88	8.74	6.4	R13
	1	124	88.9	50.8	17.5	4	20	70.0	50.80	8.74	6.4	R16
	1 1/4	133	98.4	63.5	19.5	4	20	79.5	60.32	8.74	6.4	R18
	1 1/2	156	114.3	73.0	22.5	4	23	90.5	68.28	8.74	6.4	R20
	2	165	127.0	92.1	25.5	8	20	108.0	82.55	11.91	8.0	R23
900	1/2	121	82.5	34.9	22.5	4	23	60.5	39.67	8.74	6.4	R12
	3/4	130	88.9	42.9	25.5	4	23	66.5	44.45	8.74	6.4	R14
	1	149	101.6	50.8	29.0	4	26	71.5	50.80	8.74	6.4	R16
	1 1/4	159	111.1	63.5	29.0	4	26	81.0	60.32	8.74	6.4	R18
	1 1/2	178	123.8	73.0	32.0	4	29	92.0	68.28	8.74	6.4	R20
	2	216	165.1	92.1	38.5	8	26	124.0	95.25	11.91	8.0	R24
1500	1/2	133	88.9	34.9	30.5	4	23	65.0	42.88	8.74	6.4	R13
	3/4	140	95.2	42.9	32.0	4	23	73.0	50.80	8.74	6.4	R16
	1	159	107.9	50.8	35.0	4	26	82.5	60.32	8.74	6.4	R18
	1 1/4	184	130.2	63.5	38.5	4	29	101.5	72.24	11.91	6.4	R21
	1 1/2	203	146	73.0	44.5	4	32	114.5	82.55	11.91	6.4	R23
	2	235	171.4	92.1	51.0	8	29	133.5	101.60	11.91	8.0	R26

PN (MPa)	DN	A	B	C	D	T	f	f1	Bolt Hole		Ring Type Joint			
									N	φ	K	P	F	E
1.6	10	90	60	40	-	14	2	-	4	14	-	-	-	-
	15	95	65	45	-	14	2	-	4	14	-	-	-	-
	20	105	75	55	-	14	2	-	4	14	-	-	-	-
	25	115	85	65	-	14	2	-	4	14	-	-	-	-
	32	135	100	78	-	16	2	-	4	18	-	-	-	-
	40	145	110	85	-	16	3	-	4	18	-	-	-	-
2.5	50	160	125	100	-	16	3	-	4	18	-	-	-	-
	10	90	60	40	35	16	2	4	4	14	-	-	-	-
	15	95	65	45	40	16	2	4	4	14	-	-	-	-
	20	105	75	55	51	16	2	4	4	14	-	-	-	-
	25	115	85	65	58	16	2	4	4	14	-	-	-	-
	32	135	100	78	66	18	2	4	4	18	-	-	-	-
4.0	40	145	110	85	76	18	3	4	4	18	-	-	-	-
	50	160	125	100	88	20	3	4	4	18	-	-	-	-
6.3	10	100	70	50	35	18	2	4	4	14	50	35	9	6.5
	15	105	75	55	40	18	2	4	4	14	55	35	9	6.5
	20	125	90	65	51	20	2	4	4	18	68	45	9	6.5
	25	135	100	78	58	22	2	4	4	18	78	50	9	6.5
	32	150	110	82	66	24	2	4	4	23	82	65	9	6.5
	40	165	125	95	76	24	3	4	4	23	95	75	9	6.5
10.0	50	175	135	105	88	26	3	4	4	23	105	85	12	8
	10	100	70	50	35	18	2	4	4	14	50	35	9	6.5
	15	105	75	55	40	20	2	4	4	14	55	35	9	6.5
	20	125	90	68	51	22	2	4	4	18	68	45	9	6.5
	25	135	100	78	58	24	2	4	4	18	78	50	9	6.5
	32	150	110	82	66	24	2	4	4	23	82	65	9	6.5
16.0	40	165	125	95	76	26	3	4	4	23	95	75	9	6.5
	50	195	145	112	88	28	3	4	4	25	112	85	12	8
	15	110	75	55	40	24	2	4	4	18	52	35	9	6.5
	20	130	90	62	51	26	2	4	4	23	62	45	9	6.5
	25	140	100	72	58	28	2	4	4	23	72	50	9	6.5
	32	165	115	85	66	30	2	4	4	25	85	65	9	6.5
16.0	40	175	125	92	76	32	3	4	4	27	92	75	9	6.5
	50	215	165	132	88	36	3	4	8	25	132	95	12	8