



XINXIA PROUCT DATA SHEET

I. Basic data


Material: PE chemical foaming

Process: Chemical low foaming

Color: White

Specification: $\phi 39.3 * 1.0\text{mm}$

II. Composition of gaskets



Section	Material	Nominal thickness
1	PE foam layer	1.0mm

III. Multilevel data

Appearance: Visually white, no burrs, no obvious black spots, smooth incision

Size: vernier caliper, $\phi 39.3 \pm 0.2\text{mm}$ Thickness: vernier caliper: Thickness $1.0 \pm 0.2\text{mm}$

Fluorescence agent: None

Hardness: (Shore hardness) 80 ± 5

Features: With non-toxic, tasteless, odorless, independent bubble characteristics, with pearl luster light weight, rich slow elasticity, oil resistance, with excellent vacuum property.

Density specific gravity: Between 0.4-0.5

新夏塑料包装有限公司

Xinxia Plastic Packaging Co., Ltd.

地址: 江苏省昆山市石孟路169号正源创汇科技产业园6号厂房

Plant No. 6, Zhengyuan Chuanghui Science and Technology Industrial Park, No. 169 Shitmeng Road, Kunshan City, Jiangsu Province

浙江省绍兴市越城区沥海工业园区城东路3-5号

No. 3-5, Chengdong Road, Lihai Industrial Park, Yuecheng District, Shaoxing City, Zhejiang Province