



XINXIA PRODUCT DATA SHEET

I. Product technical indicators

Test item	unit	5 times	10 Times	20 Times	30 Times
Unit weight	g/cm ³	0.2	0.1	0.05	0.033
Tensile strength	Mpa	1.6	0.8	0.5	0.25
Elongation	%	230	180	160	140
Tear strength	KN/m	6.0	3.8	2.2	1.4
Compressional strength (50%)	Kg/cm ²	2.2	1.5	0.5	0.3
Water absorption	g/cm ²	0.01	0.01	0.01	0.01
Dimensional changerate (70 °C ,22h)	%	-0.7	-0.9	-1.5	-2.2
Thermal conductivity	W/m.k	—	—	0.041	0.040
Product specification	conventional type	Modified type		Flame-retardant type (Z)	
Volume weight g / cm ³	0.20-0.030	0.20-0.030	0.20-0.030	0.20-0.035	
thickness	From 5 times to 35 times each time	From 5 times to 35 times each time	From 5 times to 30 times each time		
length	0.1-10				
Width (mm)	According to the user and multiplier are 50m /volume, 100m / volume and 200m / volume respectively				
Color	15 times under 1.2m, 15,800 over 100,1000,1200,1500				
	According to the user needs (white, red, black, yellow, green, orchid, etc.)				
	Flame retardant products flame retardant : off-fire self-extinguishing				

新夏塑料包装有限公司
Xinxia Plastic Packaging Co., Ltd.

地址: 江苏省昆山市石孟路169号正源创汇科技产业园6号厂房

Plant No. 6, Zhengyuan Chuanghui Science and Technology Industrial Park, No. 169 Shitmeng Road, Kunshan City, Jiangsu Province

浙江省绍兴市越城区沥海工业园区城东路3-5号

No. 3-5, Chengdong Road, Lihai Industrial Park, Yuecheng District, Shaoxing City, Zhejiang Province