

XINXIA PROUCT DATA SHEET

I. Basic data

Material: Pressure sensitive gasket Process: Foaming, gluing, printing

Color: White, black Specification: /

II. Composition of gaskets



Section	Material	Nominal thickness
1	Printing layer	/
2	PS foaming layer	/
3	Sealed bond layer	/

III. Multilevel data

Product description

- 1. the pressure sensitive gasket belongs to a single piece of pressure induction bonding gasket, non-toxic, tasteless, strong sealing, good chemical properties.
- 2. pressure sensitive gasket can seal plastic bottles (PE, PET, PP, PS, etc.), glass bottles, metal bottles and hoses.
- 3. pressure sensitive gasket is suitable for sealed packaging of solid, colloidal, dry powder, particles and other products in the bottle;
- 4. pressure sensitive gasket used in medicine, health care products, food, cosmetics and other industries sealed packaging;
- 5. the pressure sensitive gasket in use does not need to add any equipment, with simple operation, easy to use and good sealing performance.
- 6. pressure sensitive gasket can print customer patterns, text and other information;

Usage method:

Put the pressure sensitive gasket at the bottom of the bottle cap (the printing face faces the bottom of the bottle cap, the blank face faces the mouth of the bottle); tighten the bottle cap (more than 2 hours); screw open the bottle cap, pressure sensitive gasket and bottle mouth to form a strong seal;

Product attributes:

1. pressure sensitive gasket thickness:1.0mm;0.6mm

2. pressure sensitive gasket coil width :330mm, 350mm

新夏塑料包装有限公司

Xinxia Plastic Packaging Co., Ltd.

地址: 江苏省昆山市石孟路169号正源创汇科技产业园6号厂房

Plant No. 6, Zhengyuan Chuanghui Science and Technology Industrial Park, No. 169 Shitmeng

Road, Kunshan City, Jiangsu Province

浙江省绍兴市越城区沥海工业园区城东路3-5号

No. 3-5, Chengdong Road, Lihai Industrial Park, Yuecheng District, Shaoxing City, Zhejiang Province