

Filter Paper

Qualitative Filter Paper



Introduction

- ▶ Made of 100% alpha cotton cellulose; Ash content 0.1%.
- ▶ Stable from PH 0~12; thermostable up to 120°C.
- ▶ Divided into fast, middle and slow speed.
- ▶ Diameter ranges from 7cm~18cm, and 60cm*60cm.
- ▶ Widely used in general laboratory filtration, liquid clarifications, analytical separations.
- ▶ Air and water analysis, rough sample preparation.

Product Specifications

Weight	Speed	Retention (μm)	Filtration Speed(s)	Diameter & Size	Ash Content(<%)
80g/m ² (±4)	Fast	20~25	≤35	7, 9, 11, 12.5, 15, 18, 60*60cm	0.15
	Middle	15~20	35-70(Contain)	7, 9, 11, 12.5, 15, 18, 60*60cm	0.15
	Slow	10~15	70-140(Contain)	7, 9, 11, 12.5, 15, 18, 60*60cm	0.15

Order Information

	70mm	90mm	110mm	125mm	150mm	180mm	60*60cm
Slow	QL0700S	QL0900S	QL1100S	QL1250S	QL1500S	QL1800S	QL6600S
Medium	QL0700M	QL0900M	QL1100M	QL1250M	QL1500M	QL1800M	QL6600M
Fast	QL0700F	QL0900F	QL1100F	QL1250F	QL1500F	QL1800F	QL6600F

Package: 100pcs/pk